



MODULE n°6

NPP Siting, Design, Construction, Operation and Decommissioning

APPROACH TO SITE SELECTION UNICEN GUIDELINES DESCRIPTION



Corrado Alessandroni - Ansaldo Nucleare - Licensing and System Integration

March 16, 2012





THE OBJECTIVES

OBJECTIVES OF THE PRESENTATION

Present the guidelines produced by UNICEN GdL 1b (Task Group 1b) to support the NPP site selection process in Italy

UNICEN Commissione tecnologie nucleari e radioprotezione UNI (Ente nazionale italiano di unificazione)





GdL 1b – Background

- Working period 2009 (March September)
 (document draft issued end of September 2009)
- Nuclear option considered by the Italian Government (Legge Delega N⁹9 del 23-7-2009)
- 11 organizations about 30 experts involved (ISPRA, MinSvEcon, ENEL, ACEA Electrabel, EDISON, EON, TERNA, SOGIN, ENEA, CESI/RSE, ANSALDO NUCLEARE)





GdL 1b - Scope of Work

Provide Guidelines and Plant Information to support the licensing process of new generation NPP to be built in Italy

- 1.Definition of site selection parameters and related criteria starting from the study done in 1977 by the Italian Safety Authority [CNEN-DISP DISP(1977)] and updating considering:
 - ➤ The features of new NPP design (Generation III Reactors)
 - > IAEA more updating safety requirements
- 2. Definition of new generation NPPs site parameter envelope data
- 3. Considerations on site related issues relevant for the Italian situation (e.g. Site sharing with existing NPPs under decommissioning o Power generation plants)

For the Environmental Protection Issue the guide reports only generic consideration because detailed analyses were allocated in another workgroup (GdL 22)





GdL 1b - Scope of Work

SITING CRITERIA





Exclusionary criteria

Attention (Non-exclusionary) criteria

Site Parameter Envelope

Siting near other plants





Definition of site selection parameters and related criteria

Reference Nuclear Power Plant Design

- Generation III NPP (e.g. AP1000-1000MWe and EPR-1600 MWe)
- EUR document NPP design envelope as technical reference
 - □ European Utility Requirement document (EUR document) is a nuclear power plant specification written by a group of of European electricity producers willing to keep the nuclear option open (Enel and Sogin in the group).
 - ☐ EUR document common frame for development of next generation LWR NPPs.
 - ☐ Starting work in 1992






Definition of site selection parameters and related criteria

Exclusionary Criteria

- 1. Population density and use characteristics of the site environs
- 2. Seismology and geology







Population density and use characteristics of the site environs

Area is acceptable for NPP installation if:

1.≤ 3 km around NPP

- Resident population density equivalent to the national average at km²
- No special large structures with people difficult to relocate (even temporary) -(e.g. Hospital, Prisons,)
- 2.It is possible to put under nuclear operator control an Area ≤ 800 m around NPP

Preferential factors:

- 1.Distance of towns with 50.000 to 250.000 people ≥ 5 km
- 2.Distance of towns with more than 250.000 people ≥ 10 km





Population density and use characteristics of the site environs

RATIONALE – ref. EUR Vol.2 Chapter 1 Safety Goals

- Significant reduction of the radiological impact on environment even in severe accident conditions
- Emergency Plan simplification
- Limited impact on local economy (i.e. restrictions on the consumption of foodstuff and crops limited in terms of timescale and ground area.)





Population density and use characteristics of the site environs

RATIONALE – ref. EUR Vol.2 Chapter 1 Goals for Severe Accidents

"Three objectives related to direct PUBLIC INVOLVEMENT in case of accident:

- no Emergency Protection Action beyond 800 m from the reactor during releases from the containment;
- > no Delayed Action at any time beyond about 3 km from the reactor;
- no Long Term Action at any distance beyond 800 m from the reactor.





Seismology and Geology

General screening

Area is acceptable for NPP installation if:

- Not affected by volcanism and active faults
- ➤ Earthquake peak ground acceleration ≤ 0,3 g with reference to rock soil and event return time of 2475 years (ref. D.M. 14-1-2008 NTC)

■ More detailed screening for selected areas

Verification if **geotechnical hazards** (i.e. soil liquefaction, behavior of foundation materials, slope instability, site surface collapse, subsidence or uplift) of selected areas cannot be managed by reasonable compensating engineering safeguards (risk of unproven design solutions or significant departure from NPP standard design)





Definition of site selection parameters and related criteria

Attention (Not Exclusionary) Criteria

- 1. Meteorology and hydrology
- 2. Man-related hazards
- 3. Infrastructures and site accessibility





Meteorology and Hydrology

Factors normally not critical for site selection

- Reference plant addresses most of natural events even the extremes ones (e.g. tornadoes, raining storms)
- Where unfavorable physical characteristics exist, the site may be accepted if reasonable compensating engineering safeguards may be implemented avoiding risk of unproven design solutions or significant departure from NPP standard design

The risk flooding can make unsuitable the selected areas

Attention should be given to:

- Narrow valleys surmounted by: lakes, dikes, water basins
- Areas subject to: landslides, avalanches, snowslides (also induced only by earhquakes)
- Coastal areas subjected in the past to seaquakes





Man-related hazards

Generation III reactors (EUR) are designed to withstand special external manmade events like: aircraft impact, pressure waves and toxic clouds.

ATTENTION CRITERIA:

A. AIRPORTS

- 1. Military Airports: 15 km from runways and 8 km from airport area
- 2. Commercial airports: 8 km from airport area (1/2 for small airports with aircraft velocity less than 250 km/h
- B. MILITARY INSTALLATIONS: 8 km from area boundary of important firing grounds and military exercises area
- C. INDUSTRIAL INSTALLATIONS: case-by-case evaluation of installation within 8 km





Infrastructures and site accessibility (1)

- 1. WATER SOURCES
- 2. AREAS REQUIRED FOR PLANT CONSTRUCTION
- 3. SITE ACCESSIBILITY (Transportation of big equipment: weight and dimensions)
- 4. ELECTRICAL GRID CONNECTION





Infrastructures and site accessibility (1)

1. WATER SOURCES

Cooling water for main condenser and plant component cooling

Roughly for 1000 MWe: 35÷40 m³/s

Potable and industrial water

Roughly for 1000 MWe: 5÷10 m³/h and 20÷70 m³/h respectively

2. AREAS REQUIRED FOR PLANT CONSTRUCTION

Plant area + Construction servicing areas: equipment temporary storage areas, workshops, offices, canteens ..

Plant specific; roughly 16 to 33 hectares per unit





Examples for a 1000 MWe NPP

Infrastructures and site accessibility (2)

3. SITE ACCESSIBILITY (Transportation of big equipment: weight and dimensions)

WEIGHT		Spent Fuel Cask:	100 t
	•	Steam Generator:	640 t
	•	Turbine Rotor	150 t
	•	Turbine Stator	450 t
DIMENSION			
DIMENSION	•	Vessel	7,3 x 12 m
	•	Steam generator	6,6 x 27 m
	•	Turbine Rotor	6 x 10 m
	•	Turbine Stator	6 x 13 m





Infrastructures and site accessibility (3)

- ELECTRICAL GRID CONNECTION: availability of suitable connections near the NPP
 - Power sources to the plant assured by at least two physically separated circuits in order to minimize the probability of concurrent failure occurrences.
 - Possibility to connect the plant at least to one circuit of 132/150 kV independent from the line used for electric power transmission by the plant (IAEA Safety Guide 50-SG-D7)





Site sharing with other installations

Shared Sites

- NPP sharing the site with NPP under decommissioning or other Nuclear Installation
 - site already qualified for nuclear use
 - utilization of some existing structures and infrastructures (transportation roads grid connections)
 - Verification of the accomplishment of radiological commitments and accident consequences by adding a new installation
- NPP sharing the site with conventional power plant
 - utilization of some existing structures and infrastructures (transportation roads grid connections)
 - verification of the NPP radiological impacts on conventional activities both in normal and accident situations
 - plants separation for security reasons





NPP site parameter envelope data



COLLECTION OF DATA FROM EUR DOCUMENT





NPP site parameter envelope data

Tabella 1 - Condizioni Standard di SITO (Rif. EUR par. 2.4.1.4)

Parametro	Valori	Periodo
Temperatura ed Umidità dell'Aria E stema:		
Massime temperature Lungo Periodo Breve Periodo-Biornalmente Istentanea Minime temperature Lungo Periodo Breve Periodo-Biornalmente Istentanea Massima unidità di progetto	32 °C 37 °C 42 °C - 25 °C - 30 °C - 35 °C	> 7 giorni da 6 ha 7 giorni O h > 7 giorni da 6 ha 7 giorni 8 h
- Estate - Inverno	60 % a 37 °C (Bulbo Secco) 100 % a - 25 °C	
Vento:	Maximum values	
■ Base ■ Estremo	43 m /s 70 m /s	
Sisma Accelerazione riferita alla superfice indisturcata del terreno	0,2£g	
Sto marino Sto fluviale con torri di raffreddamento	Minimo Messimo -0,5 °C 33 °C 0 °C 33 °C	

EUR – Site Parameter Envelope Extract from GdL 1b Draft document






Decreto Legislativo N°31 – 15/2/2010 - Art. 8: Parametri Esplicativi dei Criteri Tecnici Valutazione dei Siti

Parametri riferiti ai seguenti profili:

- Popolazione e fattori socio-economici
- Idrologia e risorse idriche
- Fattori meteorologici
- Biodiversità
- Geofisica e geologia
- Valore paesaggistico
- Valore architettonico storico
- Accessibilità
- Sismo-tettonica
- Distanza da aree abitate e da infrastrutture di trasporto
- Strategicità dell'area per il sistema energetico e caratteristiche della rete elettrica
- Rischi potenziali indotti da attività umane nel territorio circostante


















ZONE	ACCELERAZIONE DI PICCO (ag)
1	ag< 0,05g
2	0,15g> ag≥ 0,05g
3	0,25g> ag≥ 0,15g
4	0,3g> ag≥ 0,25g
š	ag>0,3g

Exclusionary criterion

Areas Seismic classification

Zone 5 Excluded










Figura 4- Comuni con densità superiore alla media nazionale

Exclusionary Criterion
Population Density
higher than national average




Figura 5- Aree urbanizzate con densità di popolazione superiore alla media nazionale per km quadrato





Results of the application of the exclusionary criteria





Figura 7- Aree idonee risultanti dai criteri di esclusione di riferimento





Figura 9- Aree idonee risultanti dai criteri di esclusione e non esclusione di riferimento

Process for NPP site selection










Figura 10- Aree idonee risultanti dai criteri di esclusione e opportunità (in giallo: aree già idonee nel '77valutazione ENEA; in rosa: aree non previste dalla valutazione del '77)







EXCLUSIONARY CRITERIA

- GeoHazards
- Surface Faulting and potential liquefaction
- 3. Other natural Hazards
- 4. Cooling water source
- 5. Population density
- 6. -NA-
- 7. -NA-

- GeoHazards
- Surface Faulting and potential liquefaction
- Other natural Hazards
- Cooling water source
- Population density
- 6. Restricted areas
- 7. Site size

- GeoHazards
- 2. -NA-
- 3. Other natural Hazards
- 4. Cooling water source
- Population density
- 6. -NA-
- 7. Site size

NOT-EXCLUSIONARY CRITERIA

- Extreme events from human activities
- 2. Transportation access
- 3. Grid system
- Landscape and
- Ecological issues
- Extreme events from human activities
- 2. Transportation access
- 3. Grid system
- Landscape and Ecological issues
- Extreme events from human activities
- 2. Transportation access
- Grid system
- Landscape and Ecological issues

